

# KROY®

# K4652/K4653

## POWERFUL INDUSTRIAL PRINTERS

The new K4652 and K4653 series of industrial label printers are equally at home in the office, warehouse and manufacturing environments. Featuring an all metal construction, these two new additions to the Kroy range are built to withstand the day to day rigours of industrial use.

Combined with our extensive range of labels and printer ribbons, both models offer quality performance, low operating costs and outstanding value for money.



### Features include..

Package includes, CD, ribbon for TT, label (TT or DT), USB cable and quick installation guide  
Labelview XLT+, Windows driver for 95, 98, NT, 2000, XP

### Technical specification:

Size: 301mm (W) x 420mm (H) x 241mm (L)  
Weight: 13Kg  
Memory: 3Mb, 2Mb DRAM, 1 Mb flash  
Sensors: Label gap, paper end, black mark  
Output: 100-240V universal switching gear

CE, FCC class A, UL, CUL, TUV  
CE class B (EN60950), EN55022, EN55024,  
EN1000-3-2, EN61000-3-3), FCC class B, VCCI  
Input: 115/230 VAC, 60/50 Hz  
Operating temperatures: 5°C -35°C

Font: Five alpha-numeric fonts, OCR-A, OCR-B, and one true type font  
Barcode: Code 39, 39C 93, 128UCC, 128 subsets A, B, C, Code 11 Codabar, Interleaved 2 of 5, EAN-8, 13, 128, UPC-A, UPC-E, EAN and UPC 2(5) digitals add-on, C POST, MSI, Plessey, Postnet  
2-D barcode: PDF-417, Maxicode, DataMatrix

### Options:

Cutter: 102mm width (paper thickness upto 0.25mm)  
Interfaces: USB, RS-422/485, Internal Ethernet adapter

1Mb onboard flash (expandable to 8Mb)  
KU-007 plus keyboard display unit

### Printing

Thermal transfer/direct thermal printing  
Resolution: K4652: 8 dots per mm 203dpi  
K4653: 12 dots per mm 300dpi  
Print speed: K4652: upto 6 IPS,  
K4653: upto 4 IPS

Max. print width: 6mm - 108mm  
Max. print length: 990mm depending on user software limitations

### Media:

Roll and label (die-cut, continuous, fan fold, ticket)  
Media thickness: 0.06mm - 0.25mm  
Media width: 25.4mm - 116mm  
Media diameter (max.): 203mm with 25mm, 76mm core

Ribbon core diameter: 25.4mm  
Ribbon width: 25.4mm  
Ribbon length (max.): 300mm  
Supply roll holder: Internal

Our recommendations on the use of our products are based on test data believed to be reliable, but we would ask that you conduct your own tests to determine the suitability for your application. Kroy cannot accept any liability, direct or consequential for loss or damage caused as a result of our recommendations. Specifications and pricing may change at any time without notice. Subject to product availability. ©1994 Kroy (Europe) Ltd. Kroy and DuraType are registered trademarks of Kroy Inc.

## KROY®

Kroy (Europe) Limited  
Unit 2, 14 Commercial Way  
Reading, Berkshire, RG2 0QJ England  
Tel +44 (0)118 9865 200 Fax +44 (0)118 9865 205

www.kroyeurope.com e-mail info@kroyeurope.com

France  
Service Commercial Tel +33 1 48 69 58 18  
Germany  
Kundendienst Tel +49 2464 907142

